Air Conditioning

Product Information

PEAD-RP50JAQ (Single Phase)
Power Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference



Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

Key Features

- Reduced height entire range only 250mm
- Wider range of external static pressure settings across entire range
- Drain pump included as standard





Air Conditioning | Heating Ventilation | Controls



PEAD-RP50JAQ (Single Phase)
Power Inverter Heat Pump
Ceiling Concealed Ducted System

Product Information

Making a World of Difference


Air Conditioning

PEAD-RP - INDOOR UNITS		PEAD-RP50JAQ
CAPACITY (kW)	Heating (nominal)	6.0 (2.5-7.3)
	Cooling (nominal)	5.0 (2.3-5.6)
	Heating (UK)	5.1 (2.15-6.2)
	Cooling (UK)	4.6 (2.1-5.15)
SHF (nominal & UK)		0.84
COP / EER (nominal)		4.00 / 3.47
SCOP / SEER (BS EN14825)		4.3 / 5.5
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A+ / A
AIRFLOW (I/s)	Lo-Mi-Hi	200-242-283
PIPE SIZE mm (in)	Gas	12.7 (1/2")
	Liquid	6.35 (1/4")
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Mi3-Hi	26-31-35
SOUND POWER LEVEL (dBA)		57
DIMENSIONS (mm)	Width x Depth x Height	900 x 732 x 250
WEIGHT (kg)		28
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP50VKA
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		46 / 44
SOUND POWER LEVEL (dBA) Heating/Cooling		65
WEIGHT (kg)		46
DIMENSIONS (mm)	Width x Depth x Height	809 x 300 x 630
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	1.50 / 1.44
	Heating/Cooling (UK)	1.28 / 1.28
STARTING CURRENT (A)		5.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		7.65 / 7.09 [14.4]
FUSE RATING (BS88) - HRC (A)		16
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		2.4



Front View Upper View Suspension bolt hole 4-14x30 Siot Air (lifet lifet lif



Side View

 Model
 A
 B
 C
 D
 E
 F

 PEAD-RP50JAQ
 900
 954
 1000
 860
 9
 800



Telephone: 01707 282880

 $email: air.conditioning@meuk.mee.com \\ web: www.airconditioning.mitsubishielectric.co.uk$

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Country of origin: United Kingdom — Japan — Thialand — Malaysia. (Mittaubish) Electric Europe 2015. Mitsubish and Mitsubish and Mitsubish or preserves the right to make any variation in technical specification for the equipment described, or to withdraw or replace products without prior notification or public amonoment. Missubish Electric is constraintly developing and improving its products. All descriptors, likistations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on equest. Third-party product and brand anness may be traders or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment





