Air Conditioning

Product Information

PEAD-RP60JAQ (Single Phase)
Power Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference



Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

Key Features

- Reduced height entire range only 250mm
- Wider range of external static pressure settings across entire range
- Drain pump included as standard





Air Conditioning | Heating Ventilation | Controls



Dr

PEAD-RP60JAQ (Single Phase)
Power Inverter Heat Pump
Ceiling Concealed Ducted System

Product Information

DIMENSIONS

Making a World of Difference

Air Conditioning


PEAD-RP - INDOOR UNITS		PEAD-RP60JAQ	
CAPACITY (kW)	Heating (nominal)	7.0 (2.8-8.2)	
	Cooling (nominal)	6.1 (2.7-6.7)	
	Heating (UK)	5.95 (2.4-6.95)	
	Cooling (UK)	5.5 (2.5-6.15)	
SHF (nominal & UK)		0.83	
COP / EER (nominal)		3.91 / 3.70	
SCOP / SEER (BS EN14825)		4.1 / 5.8	
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A+	
AIRFLOW (I/s)	Lo-Mi-Hi	242-300-350	
PIPE SIZE mm (in)	Gas	15.88 (5/8")	
	Liquid	9.52 (3/8")	
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150	
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Mi3-Hi	25-29-33	
SOUND POWER LEVEL (dBA)		55	
DIMENSIONS (mm)	Width x Depth x Height	1100 x 732 x 250	
WEIGHT (kg)		33	
ELECTRICAL SUPPLY		Fed by Outdoor Unit	
FUSE RATING (BS88) - HRC (A)		6	
INTERCONNECTING CABLE No. Cores		4	

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP60VHA
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		48 / 47
SOUND POWER LEVEL (dBA) Heating/Cooling		67
WEIGHT (kg)		67
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	1.79 / 1.65
	Heating/Cooling (UK)	1.47 / 1.52
STARTING CURRENT (A)		5.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		9.76 / 8.68 [20.6]
FUSE RATING (BS88) - HRC (A)		25
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		3.5



Front View Upper View Suspension bolt hole 4-14x30 Slot 4-14x30 Slot Air Indied Grand Quies Grand Grand

Side View



 Model
 A
 B
 C
 D
 E
 F

 PEAD-RP60JAQ
 1100
 1154
 1200
 1060
 11
 1000



Telephone: 01707 282880

 $email: air.conditioning@meuk.mee.com \\ web: www.airconditioning.mitsubishielectric.co.uk$

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Courts of origin: United Kingdom — Japan — Thailand — Malaysia. (Mitsubish Bectric Europe 2015. Mitsubish) and Mitsubish let Electric are trademarks of Missubish Eschric Europe B.V. The company reserves the right to make any availation in technical specification to the equipment described, or to withdrawor replace products without principle non-public amonoment. Missubish Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sala, a copy of which is available on equal. Third-party product and brand names may be trademarks or their respective owners.













Mitsubishi Electric UK's commitment to the environment





