Product Information

Ventilation

VL-100(E)U₅-E Total Heat Exchanger Making a World of Difference









LOSSNAY		RESIDENTIAL WALL - MOUNTED VL-100(E)U ₅ -E
Electrical Power Supply		220-240V, 50Hz
Phase		Single
Power Consumption (W)	Low	17
	High	34
Airflow (m³/h)	Low	61
	High	106
Sound Pressure Level (dBA)	Low	27
	High	38
Temperature Exchange Efficiency (%)	Low	79
	High	72
Weight (kg)		7.5
Dimensions (mm)	Width	620
	Depth	200
	Height	265
Duct Size (mm)		2 x 075
Fuse Rating (BS88) - HRC (A)		6
Mains Cable No. Cores		3

^{*1} The VL-100U₅-E includes a pull cord switch to control the unit.


NOTE: The VL-100EU₅-E is available without a pull cord switch and with the option to fit a field supplied external wall switch.


VL-100(E)U₅-E DIMENSIONS





WIRING DIAGRAMS







Telephone: 01707 282880

email: ventilation@meuk.mee.com website: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

ctric Europe 2013. Misubishi and Mitsubishi Electric are trademarks of Misubishi Electric Europe B.V. The company reserves the to withdraw or replace products without prior notification or public announcement. Misubishi Electric is constantly developing are in this publication present only experie particulars and shall not from part of any contract. All goods are supplied subject to Third-party product and brand names may be trademarks or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment







Connect with Green Gateway

